



Phone: 916-638-7718 Fax: 916-638-2450

4700 Lang Ave, Suite D, Mcclellan, CA 95652

Hydraulic Initial-Pinch Plate Bending Rolls with Power Rear Roll Adjustment

Model SRH





Hydraulic drop end

TECHNICAL SPECIFICATIONS AND STANDARD FEATURES

- Steel welded main frames
- Hydraulic drop end
- Mobile control panel
- Motor powered centralized rolls
- Hydraulic rear roll
- Main motor with brake system
- Planetary gearbox driven
- Cone bending
- Support system for top roll
- Rear roll journalled in roller bearings
- Built according to EC safety directives (CE mark)
- SAE 1050 certificated steel rolls with high tensile strength
- Induction hardened rolls
- Two digital read-outs









Standard control panel with digital readouts















MODEL	CAPACITY (mild steel)	DIAMETER of the rolls
SRH-3-80	3' x 12 ga.	3.15"
SRH-4-80	4' x 14 ga.	3.15"
SRH-4-100	4' x 11 ga.	3.94"
SRH-4-130	4' x 3/16"	5.12"
SRH-4-150	4' x 1/4"	5.91"
SRH-4-180	4' x 3/8"	7.09"
SRH-4-200	4' x .47"	7.87"
SRH-5-80	5' x 16 ga.	3.15"
SRH-5-100	5' x 14 ga.	3.94"
SRH-5-130	5' x .18"	5.12"
SRH-5-150	5' x 1/4"	5.91"
SRH-5-180	5' x .35"	7.09"
SRH-5-200	5' x 7/16"	7.87"
SRH-5-220	5' x .47"	8.66"
SRH-5-250	5' x .59"	9.84"
SRH-6-130	6' x 5/32"	5.12"
SRH-6-150	6' x .24"	5.91"
SRH-6-180	6' x 5/16"	7.09"
SRH-6-200	6' x 3/8"	7.87"
SRH-6-220	6' x 7/16"	8.66"
SRH-6-250	6' x .47"	9.84"
SRH-8-150	8' x 5/32"	5.91"
SRH-8-180	8' x .24"	7.09"
SRH-8-200	8' x 5/16"	7.87"
SRH-8-220	8' x .35"	8.66"
SRH-8-250	8' x 3/8"	9.84"
SRH-10-180	10' x 5/32"	7.09"
SRH-10-200	10' x .24"	7.87"
SRH-10-220	10' x 5/16"	8.66"
SRH-10-250	10' x .35"	9.84'

