

Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, Mcclellan, CA 95652



This aggressive belt grinder features a 3×79 inch belt track with heavy steel construction to deliver material finishing with the quiet, smoothness that customers expect from a quality grinding machine year after year.

- 3" x 79" belt track
- 7200 surface feet per minute (SFPM) belt speed
- 3 or 5 horsepower American made motors UL/CSA variable speed option available
- Swing frame grinding option
- Heavy welded steel construction with cast iron accessories
- 8" diameter 70 durometer serrated contact wheel with deep groove sealed ball bearings
- Integrated, heavy steel pedestal with optional elevation control
- Ventilated 4" x 18" steel platen
- 3" Hose Outlet



Model 979 adapts as a swing grinder.

Shown with optional mag starter. Pedestal included.



Optional Magnetic starter and elevation control.



SAFE

- O.S.H.A. compliant belt track and pinch points guarding
- UL/CSA motors and electrical controls

OPERATOR & SHOP FRIENDLY

- Quick easy belt change with positive simple belt tracking control
- Quiet smooth running minimizes operator fatigue
- Small footprint uses less shop space

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

10