



Providing Solutions.


Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, McClellan, CA 95652

MODEL **1338**

**Manual Bandsaw
with Extended Capacity**



Manufactured in the United States of America

Wellsaw[®]

Built better to work stronger and last longer

1338

Model 1338 Manual Bandsaw



Standard Features

Spring-Loaded Carbide Guides with Rollers

Combination Reduction Gearbox and Ring & Pinion Blade Drive

Baldor® Motor

3hp Motor 3 Phase TEFC

2hp Single Phase ODP

Infinitely Variable Blade Speeds

Rite-Tension® Blade Tensioning Device

Flood Type Wet Cutting System

Powered Blade Brush

110 Volts at Controls

Overload and Undervoltage Protection

Precision Ground Bed and Vise Jaws

Quick Acting Vise

Adjustable Stock Stop/Back-Gauge

Auto Shut-Off at End of Cut

OSHA Blade Guarding

Tiger-Tooth® Bi-Metal Blade

Coolant for Initial Start-Up

Specifications

Capacity	Round 13" Rectangular 13" x 38" 45° Angle 12" x 21"
Blade Size	1" x .035" x 15'6" (186")
Blade Speeds	Infinitely Variable 70-375 SFPM
Blade Guides	Carbide Guides with Rollers
Blade Tension	Manual Rite-Tension®
Electrical Options	115-208-230/60/1 208-230-460/60/3
Coolant System	Tank Capacity 8 Gallons Submersible Pump/3 GPM
Vise Control	Quick Acting/Manual Screw
Swivel Vise	To 45°
Feed Control	Variable Hydraulic with Counterbalance Spring
Band Wheels	15" Diameter Cast Iron
Bed Height	29"
Floor Area	40"W x 102"L
Shipping Weight	1,200 Lbs.

Available Factory Installed Options

Flush Hose with 8.5 GPM Pump

Powered Frame Raise and/or Powered Vise

Laser Line Pointer

Casters (Set of 4, 2 Locking)

NFPA Electrics (with Disconnect)

Work Light with Transformer

Stock Stand, 18"

5' and 10' Non-Powered Roller Conveyor

Please Contact Factory for Additional Options

Other Models in the 1318 Family

Model 1318 13" x 18" Capacity Manual Saw

Model 1316S Swivel Head 60° Miter Saw

All Models Available with PLC Controlled Semi-Automatic Operation

Wellsaw®