

# MBS-1014W-1, 10" X 14" HORIZONTAL MITERING BANDSAW

414479

JET Mitering Horizontal bandsaws unique design features a swiveling head while the base remains stationary. This allows the stock to remain same position while making accurate crosscuts and miters. Backed by the industry leading two year warranty, JET Mitering Bandsaws are built to last and deliver precision results.



## FEATURES

- Mitering head swivels to cut any angle 0° - 45° while the work piece remains secured
- Large , easy-to-read scale for accurate positioning of the saw head
- Fully adjustable hydraulic downfeed with separate on/off control valve
- Large hand wheel and built-in gauge provides easy blade tensioning
- Carbide blade guides with roller bearings
- Coolant is distributed through the blade guides
- Quick positioning vise reduces set-up time
- Built-in, self propelled blade brush extends blade life
- Automatic shut-off after cut
- Coolant system
- Adjustable material stop
- 1" Bi-Metal blade



*Providing Solutions*

Tollfree Ph 888-906-4350  
Email: [sales@scottmachinery.com](mailto:sales@scottmachinery.com)

[www.scottmachinery.com](http://www.scottmachinery.com)

5209 Luce Avenue, Bldg. 243-B, McClellan, CA 95652



## JET RED ASSURANCE 2-YEAR WARRANTY

JET warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Service Centers located throughout the United States can give you quick service. In most cases, any of these JPW Industries Authorized Service Centers can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET tools. For the name of an Authorized Service Center in your area call 1-800-274-6848.

STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE

# MBS-1014W-1, 10" X 14" HORIZONTAL MITERING BANDSAW

414479

## SPECIFICATIONS

|                                      |                   |
|--------------------------------------|-------------------|
| Cutting Capacity (W x D) (In.)       | 10 x 14           |
| Round at 90 Degrees (In.)            | 10                |
| Round at 45 Degrees (In.)            | 9                 |
| Rectangle at 90 Degrees (In.)        | 10 x 14           |
| Rectangle at 45 Degrees (In.)        | 9 x 8-1/2         |
| Throat Depth (In.)                   | 10-1/2            |
| Vise Swivels (Deg.)                  | 45°               |
| Head Movement (Deg.)                 | 45°               |
| Blade Size (In.)                     | 1 x .035 x 130    |
| Blade Length (In.)                   | 130               |
| Blade Wheel Diameter (In.)           | 14                |
| Blade Speed (SFPM)                   | 82, 132, 210, 330 |
| Bed Height (In.)                     | 25                |
| Motor (HP)                           | 2 HP, 230V, 1Ph   |
| Drive                                | Belt Drive        |
| Overall Dimensions (L x W x H) (In.) | 26 x 69 x 44      |
| Weight (Lbs.)                        | 946               |



*Providing Solutions*

Tollfree Ph 888-906-4350  
Email: [sales@scottmachinery.com](mailto:sales@scottmachinery.com)

[www.scottmachinery.com](http://www.scottmachinery.com)

5209 Luce Avenue, Bldg. 243-B, McClellan, CA 95652

STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE