


Lathes – MLD-1030

SPECIFICATIONS – MLD-1030

SPECIFICATIONS – MLD-1030		
Lathe		
Distance Between Centers	21.5" / 29.5"	550 / 750 mm
Swing Over Bed	9.75"	250 mm
Swing Over Cross Slide	5.7"	145 mm
Width of Bed	5.3"	135 mm
Taper of Spindle Bore	MT 4	
Speed	50 – 2000 rpm / Variable	
Range of Longitudinal Feed (per rev)	.003 – .008"	.07 – .2 mm
Range of Inch Threads	8 – 56 T.P.I	
Range of Metric Threads	.4 – 3.5 mm	
Top Slide Travel	2"	50 mm
Cross Slide Travel	4.5"	115 mm
Tailstock Quill Travel	2"	50 mm
Taper of Tailstock Quill	MT 4	
Motor	1 hp	
Voltage	110V	
Mill / Drill		
Taper of Spindle Bore	R 8	
Spindle Stroke	2"	50 mm
Spindle Speed	50 – 2250 rpm / Variable	
Max. Distance Spindle to Table	11"	280 mm
Max. Distance Spindle to Column	6.5"	165 mm
Motor	.75 hp	
Voltage	110V	
Shipping Dimensions (L x W x H)	56" x 26" x 49"	1422 x 660 x 1245 mm
Shipping Weight	429 lbs.	195 kgs.

Specifications subject to change without notice.

- ◆ Combination mill, lathe, and drill
- ◆ Precision ground and hardened ways
- ◆ MT4 spindle taper on lathe
- ◆ R8 spindle taper on mill/drill
- ◆ Power longitudinal feed
- ◆ Gear driven mill head
- ◆ Digital readout for RPM of lathe
- ◆ Digital readout for depth of cut on mill head
- ◆ 110V



Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, McClellan, CA 95652