



Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, McClellan, CA 95652

W.F. WELLS MODEL H-2024-3

Specifications

Capacity.....	Rectangular @ 90° 20" H x 24" W, Round at 90° 20" Diameter	
Weight Capacity.....	5,000 lbs	
Blade Speed	60-500 SFPM	
Blade Size	1½" X .050" X 20' 0"	
Blade Guide.....	Roller Guides with Carbide Inserts	
Blade Tension.....	Hydraulic	
Bandwheel Size	22"	<u>Voltage</u>
Vise	Full Stroke Hydraulic, 15"	208-60-3
Blade Drive	10 HP, AC Vector Drive	230-60-3
Sawing Force.....	0-750 lbs	460-60-3
Coolant Capacity	15 Gallons	575-60-3
Hydraulic Capacity	20 Gallons	
Hydraulic Drive	2 HP Motor	
Work Height.....	35"	
Shipping Weight.....	3,900 lbs	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Shipping Dimensions.....	103" L x 50"W X 93"H	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Hydraulic Holddown, Manual
- Automatic Length Stop Assembly
- Discharge Worktable, 20" X 48" L with Stock Stop
- Discharge Worktable, 24" X 48" L with Stock Stop
- Work Light, Wired In
- Blade Break/Stall Switch
- Hydraulic Chip Conveyor, Auger Style
- High Speed Drive & Guides (1-¼" Blade) 400-3000 SFPM
- Free Standing Roller Stock Conveyors, 6" Centers:
 - 21" X 5' X 5,000 lbs Cap. Distributed Weight
 - 21" X 10' X 10,000 lbs Cap. Distributed Weight
 - 24" X 5' X 5,000 lbs Cap. Distributed Weight
 - 24" X 10' X 10,000 lbs Cap. Distributed Weight
- 21" X 10' Powered Conveyor, Hydraulic
- 24" Powered Conveyor

Consult Factory for Additional Accessories

*Prices and specifications subject to change without notice

