

354216 : J-2234AC 20" VS Drill Press 440V, 3Ph Inverter



Features and Benefits

- Variable spindle speeds from 65 to 2000 RPM
- MT-3 spindle taper
- Latest AC inverter variable speed technology
- High torque at all speeds both forward and reverse
- Continuous speed adjustment while in operation

Accessories

- 561702 TDC-375, Taper Mount Drill Chuck 0-3/8" x JT-2
- 561704 TDC-500, Taper Mount Drill Chuck 0-1/2" x JT-6
- 561706 TDC-501, Taper Mount Drill Chuck 0-1/2" x JT-33
- 561708 TDC-625, Taper Mount Drill Chuck 1/8"-5/8" x JT-3
- 561709 TDC-750, Taper Mount Drill Chuck 1/8"-3/4" x JT-4



Email: sales@scottmachinery.com

Phone# 916-638-7718

Website: www.scottmachinery.com

354216 : J-2234AC 20" VS Drill Press 440V, 3Ph Inverter

Specification	Value	
Part Number	354216	
Motor	2HP, 460V, 3Ph	
Number of Spindle speeds	Variable	
Range of Spindle Speeds (RPM)	65 - 2000	
Spindle Taper	MT-3	
Quill Diameter (in.)	3	
Max Distance Spindle to Table (in.)	30-1/4	
T-Slots Number and Size (in.)	2 x 5/8	
Column Diameter (in.)	4-1/2	
Base Dimensions (LxWxH/ in.)	27-1/2 x 19-1/4 x 6	
Drilling Capacity Cast Iron (in.)	1-1/2	
Drilling Capacity Mild Steel (in.)	1-3/8	
Tapping Capacity Cast Iron (in.)	7/8	
Tapping Capacity Mild Steel (in.)	3/4	
Quill Travel (in.)	6	
Table Size (in.)	22 x 18-3/4	
Distance Column to Spindle (in.)	10-7/16	
Drills to Center of Circle (in)	20	
Swing (in.)	20	
Base Work Table (in.)	14-3/4 x 11-13/16	
Table Travel (in.)	18	
Quill Feed	6	
Spindle Travel (in.)	6	
Base Slots Number & Size (in.)	2 x 5/8	
Web Description	J-2234AC 20" VS Drill Press 440V, 3Ph Inverter	
Model Number	J-2234AC	
Brand	Jet	
Height	72	inch
Width	39	inch
Length	25	inch
Net Weight	792	pound



Email: sales@scottmachinery.com
 Phone# 916-638-7718
 Website: www.scottmachinery.com