

Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, Mcclellan, CA 95652



POWER ROTARY

MODEL PR16

power series



The PR-16 power rotary is a versatile machine capable of forming numerous applications up to 16-gauge mild steel material. Standard features include variable speed control, heavy cast body with steel body stand.

A 3/4-hp gear motor provides smooth operation. The forming pressure is controlled by a crank on the top of the frame on the standard unit; an optional hydraulic powered forming pressure unit is available. Rolls are ordered separately for this unit.

Crimping, single beading, ogee beading, elbow edging, flattening, wiring, burring and turning rolls are available.

Please contact TENNSMITH for special application forming.

Power Rotary Machine	PR16
Capacity, mild steel	16 gauge/1.6 mm
Capacity, stainless steel	20 gauge/1.0 mm
Throat	10 in./254 mm
Distance, shaft center to center	2.5 in./63.5 mm
Gear ratio	3:1
Working speed variable	3 to 45 rpm
Motor	3/4 hp
Shipping weight	350 lbs./159 kg

Available option: Hydraulic depth selection.

Roll Chart – PR16	
Roll Diagram	Туре
	Elbow Edging
H	Flange
	Flattening
H	Offset
K.	Turning
) <u> </u>	Burring
<u>}</u> _[(Wiring
X	Crimping
	Ogee Beading
]~[~	Single Beading