

Specifications

Model	MS1318SA
Drive Motor	3 Hp (2.2kw)
Hydraulic Motor	.25 Hp (.19kw)
Hydraulic Oil Capacity	2 gallons (7.5 liters)
Coolant Motor Coolant Capacity Blade Speeds (Inf. Variable) Blade Size	.125 Hp (.1kw) 7.8 gallons (7.5 liters) 102-377 fpm (31-115 m/min) 1" x .035" x 13'-11" (25 x .9 x 4150mm)
Swivel Angle Range Cutting Capacity	0° to 60°
Round @ 90°	13" (330mm)
Round @ 45°	11.5" (292mm)
Round @ 60°	8.7" (220mm)
Square @ 90°	10.6" (270mm)
Square @ 45°	10.5" (268mm)
Square @ 60°	8.7" (221mm)
Rectangular @ 90°	18.5" x 10.6" (470 x 269mm)
Rectangular @ 45°	10.5" x 10.5" (268 x 268mm)
Rectangular @ 60°	8.7" x 8.7" (220 x 220mm)
Bed Height	33" (838mm)
Dimensions: Length Width Height	75" (1905mm) 34" (863mm) 55.5" (1410mm)
Net Weight	1,400 lbs (635kg)
Shipping Weight	1,850 lbs (839kg)

Design and specifications are subject to change without notice.

Clausing 13" (330mm) Semi-Automatic Swivel Head Miter Bandsaw

Features:

- Advanced hydraulic system provides dependable power for powered clamping and raising the saw head at end of cut
- Full stroke machine vise for tight clamping of any material from operator's panel
- Operator's panel pivots allowing operator to control saw from the rear of machine
- Swivel sawhead allows the operator to accurately pivot head for angle cuts from 0°, for a 90° cut, to 60°
- Carbide blade guides provide excellent stability for the saw blade
- Variable blade speed
- Power chip brush removes chips from the blade extending blade life
- Integrated coolant system
- Cast iron moveable guide arms provide rigidity and stability for an accurate cut
- Flushing hose
- Adjustable work stop
- Tool box with tools
- Manual & parts list
- Two (2) year limited warranty


Available in Manual and Automatic Models

Accessories


- Stock Stand Assembly 21" 30"
- Roller Table Assembly 10' x 18"
- Roller Table Assembly 5' x 18"
- Bandsaw Blade Tension Gauge
- SAWZIT 1 Gallon
- SAWZIT 5 Gallon

Cutting Capacities:

Capacity at 90°



Capacity at 45°





Phone: 916-638-7718 Fax: 916-638-2450